

HIGHLIGHTS

- ✓ **Rtpw Drift: < 4 mK after 100 hours at 661 °C**
- ✓ **Accuracy: ± 0.006 °C at 0.01 °C**
- ✓ **Temperature range: -200 °C to 670 °C**
- ✓ **Customized dimensions available**



OVERVIEW

AM1760 series Secondary SPRTs provide our customers reliable secondary standards that can be used daily in their labs. This SPRT features accuracy of ± 0.006 °C at 0.01 °C, short term stability of ± 0.002 °C and very low drift rate of less than 0.004 °C after 100 hours at 661 °C. Two different lengths of SPRTs are available at 12-inch and 20-inch.

The sensing element is designed to protect the platinum sensing wire from contamination at high temperatures, giving the device a high level of stability and repeatability in performance. A uniquely designed support structure and filling material provides excellent balance between the hysteresis effect, mechanical shock and thermal shock performance. This high performance probe fully meets ITS-90 criteria for reference thermometers.

FEATURES

- Temperature range: -200 °C to 670 °C
- Accuracy: ± 0.006 °C at 0.01 °C
- Long term drift: <0.004 °C after 100 hours at 661 °C
- Short term stability: 0.002 °C
- Temperature Coefficient 0.003925 $\Omega/\Omega/^\circ\text{C}$
- $W(\text{Ga}) \geq 1.11807$
- Inconel™ sheath
- Customized dimensions available

SPECIFICATIONS

Temperature Range	-200 °C to 670 °C
Resistance at 0 °C	1760 – Nominal 100 Ω 1762 – Nominal 25 Ω
Temperature Coefficient	0.003925 Ω/ Ω/°C
Accuracy	±0.007 °C at -196 °C ±0.006 °C at 0.01 °C ±0.015 °C at 420 °C ±0.025 °C at 660 °C
Long Term Drift*	±0.004 °C at TPW after 100 hours at 661 °C
Short Term Stability	±0.002 °C
Thermal Shock	±0.002 °C after 10 times thermal cycles from minimum to maximum temperatures
Self-heating	0.0015 °C at 1 mA current
Response Time	9 seconds for 63% response to step change in water moving at 3 feet per second
Measurement Current	0.5 mA or 1 mA
Sensor Length	42 mm
Sensor Location	5 mm from tip
Insulation Resistance	>1000 MΩ at room temperature
Sheath Material	Inconel™
Dimension	1760/1762-12: 0.25 inch X 12 inch (6.35 mm X 305 mm) 1760/1762-20: 0.25 inch X 20 inch (6.35 mm X 500 mm)
External Leads	Teflon™ – insulated copper wire, 4 leads, 2.5 meters
Handle Dimension	15 mm (OD) X 65 mm (L)
Handle Temperature Range**	-50 °C to 180 °C
Optional Calibration	NIST traceable calibration and data available per request: Ordering # 5007

*Long-term drift rate is for reference only. It could be affected by such facts as handling, application, and maintenance, etc.

**Handle temperature outside this range will cause damage to the probe.

ACCESSORIES

Model	Description
9001	Wooden Carrying Case for 1760/1762-12 included
9002	Wooden Carrying Case for 1760/1762-20 included